

Ground Control Station THE UNIVERSAL CONCEPT

Presented by: Oron Yam System Engineering Dep. Manager



maintaining the data needed, and of including suggestions for reducing	nection of minimation is estimated to completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar OMB control number.	tion of information. Send comments tarters Services, Directorate for Info	s regarding this burden estimate or promation Operations and Reports	or any other aspect of the control o	nis collection of information, Highway, Suite 1204, Arlington
1. REPORT DATE 2. REPORT TYPE N/A N/A			3. DATES COVERED -		
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER	
Ground Control Station THE UNIVERSAL CONCEPT				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Elbit Systems-Silver Arrow, Israel				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAIL Approved for publ	LABILITY STATEMENT ic release, distributi	on unlimited			
13. SUPPLEMENTARY NO See also ADM0016	otes 76, UAV 2002 confe	erence & Exhibition	a., The original do	cument conta	ains color images.
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFIC		17. LIMITATION OF	18. NUMBER	19a. NAME OF	
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	- ABSTRACT UU	OF PAGES 19	RESPONSIBLE PERSON

Report Documentation Page

Form Approved OMB No. 0704-0188







Engineering Approach

- Generic design that shall support easy adaptation to various payloads, data links, human-machine interface and air vehicles
- Identical mission operation consoles
- Flexible modes designation to consoles
- A redundant system design concept ensuring the safety of the A/V and mission accomplishment



Engineering Approach

- Use of main stream technology
- Use of COTS Hardware & Software
- Interoperability by easy adaptation to STANAG 4586(Standard Interfaces for UAV Control Systems)
- Scalability of the system from RVT to full scale GCS
- Redundancy and safety emphasis



Technologies & Expertise

Composite Structure

System Engineering

System/integration & Testing

Avionics (H/W, S/W)

Rotary Engines

Command & Control

Electro Optics







HFE - DESIGN CONCERNS

- Multi-function the multi-function operation requires a console that gives the operator the means to perform all relevant functions during the different stages of the mission
- Grouping due to space and manning constraints several functions should be grouped for the same operator to perform
- Attention most of the functions do not require full time operator attention especially when no malfunction occurs and only monitoring is required



GCS Positions

Mission 1





GCS Commander



Mission 2











UAV System Concept





SW Modular Components







3 TIER MODEL (Cont')



Application Logic

Data & Resources

- Manage user interaction and request application server
- · Maps, Forms, , Slides , UAV Icon
- Perform business logic & make request to DB
- Components Design distributed to classes
- · like devices, payloads, UAV, Data elements Etc

High performance access to data







Component Based Application

The design of the application components is object-oriented, each object made up of an abstract component and real components

- The abstract component represents the general object (such as a generic UAV)
- the real component represents the real object (such as the Hermes).






Component Based Application


Application components \Longrightarrow Modular application


- Easier to maintain The impact of changes and upgrades can often be isolated down to an individual application component. This isolation simplifies integration and testing.
- Easier to enhance New capabilities can be added incrementally without impact on the existing functionality usage.
- Easier to reuse





SW Architecture





Fail-Safe Design

The main design principles:

- RTC and RTC backup controlled by a hot-backup mechanism
- Similarity of the operator consoles
- Backup server for the Application Server using a clustering mechanism.
- Backup DB for the DataBase using RAID 1-level mechanism.
- Dual redundant LAN.
- Backup terminal server for the master terminal server using software mechanism in the server for handling the backup.



Safety design



Special treatment (active and tests) is conducted for each hazard and the route that leads to it.

Example -

special CRC is added to uplink messages by the function that generates them. Recheck is preformed before transmission to the air vehicle

Certification process of the HERMES family UAVs and the UGCS was started.

